



COMPRESORES HERMÉTICOS SCROLL

ALTA Y MEDIA TEMPERATURA - Monofásicos 220/240V. 50 Hz. R-407C

Código	Modelo	CV	Desplaz. cm ³ /rev	Capacidad W (ARI)	COP	Cond. (μF/V)	€
CO4650	C-SBN261H5A	3,5	55,7	9.700	2,85	60/440	1.176,22
CO4652	C-SBN301H5A	4	66,8	11.800	2,95	60/440	1.300,97
CO4654	C-SBN351H5A	4,5	77,4	13.500	2,84	70/440	1.446,88
CO4656	C-SBN371H5A	5	83,2	14.700	2,91	70/440	1.532,64
CO4663	C-SBS200H15A	5,8	93,1	16.400	2,95	70/440	1.800,75

Incluyen aparellaje eléctrico excepto relé.



C-SB Series



C-SC Series



C-SD Series

ALTA TEMPERATURA - Trifásicos 380/415V. 50 Hz. R-407C

Código	Modelo	CV	Desplaz. cm ³	Capacidad W (ARI)	COP	€
CO4651	C-SBN263H8A	3,5	55,7	9.600	2,87	1.176,22
CO4653	C-SBN303H8A	4	66,9	11.600	3,05	1.308,76
CO4655	C-SBN353H8A	4,5	77,4	13.400	2,91	1.558,26
CO4657	C-SBN373H8A	5	83,2	14.500	2,93	1.580,54
CO4658	C-SBN453H8A	6	100	17.600	3,03	1.659,62
CO4659	C-SBS235H38A	7	110,2	19.500	3,10	1.837,84
CO4660	C-SCN603H8H	8	137	24.500	3,16	2.394,76
CO4661	C-SCN753H8H	10	171,2	29.900	3,20	3.230,14
CO4662	C-SCN903H8H	12	205,4	34.900	3,09	3.341,52

Disponible versión TANDEM con un incremento del 4%. sobre precio de lista.

BOMBA DE CALOR Y AA.- EVI - Trifásicos 380/415V. 50 Hz. R-407C

Código	Modelo	CV	Desplaz. cm ³	Capacidad en Frío W	COP	Capacidad en Calor W	COP	€
CO4680	C-SBS120H38Q	3,5	55,7	9.600	2,87	11.100	3,42	1.564,54
CO4681	C-SBS145H38Q	4	66,8	11.600	3,05	13.300	3,42	1.699,14
CO4682	C-SBS180H38Q	5	83,2	14.500	2,93	16.800	3,53	1.889,66
CO4683	C-SBS205H38Q	6	96,2	17.500	3,02	16.900	3,18	2.133,02
CO4684	C-SCS295H38Q	8	137	24.500	3,16	27.600	3,54	4.136,88
CO4685	C-SCS370H38Q	10	171,2	29.900	3,20	33.700	3,58	4.279,23
CO4686	C-SCS435H38Q	12	205,4	35.200	3,15	35.000	3,21	4.735,41

ALTA TEMPERATURA - Monofásicos 220/240V. 50 Hz. R-410A

Código	Modelo	CV	Desplaz. cm ³ /rev	Capacidad W (ARI)	COP	Cond. (μF/V)	€
CO4671	C-SBN231H5E	3	35	8.600	2,42	60/440	1.180,67
CO4672	C-SBN261H5D	3,5	37,5	9.350	2,46	60/440	1.225,22
CO4673	C-SBP120H15A	3,5	39,9	9.800	2,80	60/440	1.326,13
CO4674	C-SBN301H5D	4	39,9	9.700	2,49	60/440	1.325,47
CO4675	C-SBP140H15A	4	46,4	11.600	2,85	60/440	1.426,78
CO4676	C-SBP160H15A	4,6	51,8	13.000	2,80	60/440	1.471,62

Método de arranque compresores PSC



COMPRESORES HERMÉTICOS SCROLL

ALTA TEMPERATURA - Hi-COP - Trifásicos 380/415V. 50 Hz. R-410A

Código	Modelo	CV	Desplaz. cm ³	Capacidad W (ARI)	COP	€
CO4690	C-SBP120H38A	3,5	39,6	10.000	2,87	1.326,12
CO4691	C-SBP130H38A	3,7	42,4	10.700	2,91	1.353,94
CO4692	C-SBP140H38A	4	46,4	11.700	2,91	1.426,78
CO4693	C-SBP160H38A	4,6	52	13.200	2,87	1.471,62
CO4694	C-SBP170H38A	5	54,8	13.900	3	1.555,90
CO4695	C-SBP205H38A	6	66,9	16.900	3	1.722,68
CO4696	C-SCP270H38B	8	89,2	22.400	3,03	3.385,95
CO4697	C-SCP315H38B	10	104,1	26.000	3,02	3.480,10
CO4698	C-SCP360H38B	11	120,2	29.800	3,01	3.574,24
CO4699	C-SCP400H38B	12	131,9	32.800	3,01	3.668,39
CO4700	C-SCP510H38B	15	171,2	43.900	3,18	4.245,70



C-SB Series



C-SC Series



C-SD Series

BAJA TEMPERATURA - Hi-COP - Trifásicos 380/415V. 50 Hz. R-404A

Código	Modelo	CV	Desplaz. cm ³	Capacidad W (ARI)	COP	€
CO4705	C-SCN303L8A	4	66,8	5.300	1,41	1.697,28
CO4706	C-SCN373L8A	5	83,2	6.800	1,51	1.775,06
CO4707	C-SCN453L8H	6	104	8.100	1,41	5.141,90
CO4708	C-SCN523L8H	7	120	9.250	1,45	5.232,46
CO4709	C-SCN603L8H	8	137	10.500	1,38	5.322,91
CO4710	C-SCN753L8H	10	171,2	13.050	1,48	5.485,88

COMPRESORES DC INVERTER

R-410A

Código	Modelo	CV	Desplaz. cm ³	Tensión	Capacidad W (ARI) 90Hz.	COP	€
CO4715	C-SDP190H03A	5	38	220-240V	19.000	3,2	2.778,09
CO4716	C-SDP205H03A	6	42,3	220-240V	21.200	3,2	2.841,88
CO4717	C-SDP190H02B	5	38	380-415V	19.000	3,2	2.778,09
CO4718	C-SDP205H02B	6	42,3	380-415V	21.200	3,25	2.841,88

COMPRESORES AC INVERTER

R-404A

Código	Modelo	CV	Desplaz. cm ³	Tensión	Capacidad W (ARI) 90Hz.	COP	€
CO4720	C-SCVN603L0H	8	144,1	380-415V	14.300	1,75	Consultar
CO4721	C-SCVN753L0H	10	171,2	380-415V	16.800	1,77	Consultar