



## UNIDADES CONDENSADORAS

### ALTA TEMPERATURA (Compresor Danfoss) R-12

Modelo	HP	Capacidad W Temp. evaporación			Conexiones		Calderín		Capilar	
		- 10°C	- 5°C	0°C	Línea Líquido	Línea Aspiración	Aire			
							Código	€	Código	€
FR-6B	1/6	240	300	370	1/4"	3/8"	UC0256	379	UC0259	332
FR-7,5B	1/5	280	340	420	1/4"	3/8"	UC0262	394	UC0265	347
FR-8,5B	1/4	300	380	470	1/4"	3/8"	UC0268	396	UC0271	349
FR-10B	1/4	340	420	520	1/4"	3/8"	UC0274	402	UC0277	357
FR-11B	1/3	420	520	640	1/4"	3/8"	UC0280	436	UC0283	393
SC-10B	1/3	400	490	625	1/4"	3/8"	UC0286	480	UC0289	439
SC-12B	1/3	520	630	790	1/4"	3/8"	UC0292	508	UC0295	461
SC-15B	3/8	620	760	925	1/4"	3/8"	UC0298	577	UC0301	535
SC-18B	1/2	720	870	1.075	1/4"	3/8"	UC0304	634	UC0307	560
SC-21B	3/4	840	1.010	1.230	1/4"	3/8"	UC0310	682	UC0313	645

### ALTA TEMPERATURA (Compresor Danfoss) R-22

Modelo	HP	Capacidad W Temp. Evaporación		Conexiones		Calderín		Capilar	
		- 10°C	+ 5°C	Línea Líquido	Línea Aspiración	Aire			
						Código	€	Código	€
TL-4D	1/5	265	485	1/4"	3/8"	UC0320	368	UC0323	318
FR-6D	1/4	410	780	1/4"	3/8"	UC0326	390	UC0329	345
FR-7,5D	1/3	465	865	1/4"	3/8"	UC0332	406	UC0335	359
SC-10D	1/2	725	1.270	1/4"	3/8"	UC0338	497	UC0341	447
SC-12D	5/8	895	1.495	1/4"	3/8"	UC0344	530	UC0347	479
SC-15D	3/4	1.125	1.894	3/8"	3/8"	UC0350	687	UC0353	622

### ALTA TEMPERATURA (Compresor Danfoss) R-404A/R-507

Modelo	HP	Capacidad W Temp. Evaporación		Conexiones		Calderín		Capilar	
		- 10°C	+ 5°C	Línea Líquido	Línea Aspiración	Aire			
						Código	€	Código	€
TL-4DL	1/5	235	410	1/4"	3/8"	UC2750	383	UC2753	339
FR-6DL	1/4	372	615	1/4"	3/8"	UC2756	397	UC2759	352
SC-10DL	1/3	612	1.030	1/4"	3/8"	UC2762	492	UC2765	444
SC-12DL	1/2	732	1.280	1/4"	3/8"	UC2768	507	UC2771	459
SC-15DL	5/8	915	1.605	1/4"	3/8"	UC2774	761	UC2777	694

### ALTA TEMPERATURA (Compresor Danfoss) R-134a

Modelo	HP	Capacidad W Temp. evaporación			Conexiones		Calderín		Capilar	
		- 25°C	- 10°C	+ 5°C	Línea Líquido	Línea Aspiración	Aire			
							Código	€	Código	€
TL-4G	1/10	60	145	292	1/4"	3/8"	UC0360	395	UC0363	337
TL-5G	1/8	80	190	361	1/4"	3/8"	UC0366	397	UC0369	339
FR-6G	1/6	92	235	472	1/4"	3/8"	UC0372	363	UC0375	316
FR-7,5G	1/5	110	278	541	1/4"	3/8"	UC0378	376	UC0381	331
FR-8,5G	1/4	135	321	602	1/4"	3/8"	UC0384	378	UC0387	334
FR-10G	1/4	148	334	671	1/4"	3/8"	UC0390	384	UC0393	339
FR-11G	1/3	182	410	805	1/4"	3/8"	UC0396	397	UC0399	349
SC-10G	1/3	172	392	792	1/4"	3/8"	UC0402	440	UC0405	393
SC-12G	1/3	190	502	1.004	1/4"	3/8"	UC0408	453	UC0411	403
SC-15G	3/8	239	605	1.200	1/4"	3/8"	UC0414	520	UC0417	469
SC-18G	1/2	294	703	1.415	1/4"	3/8"	UC0420	541	UC0423	492
SC-21G	3/4	351	835	1.623	1/4"	3/8"	UC0426	602	UC0429	561

### BAJA TEMPERATURA (Compresor Danfoss) R-404A

Modelo	HP	Capacidad W Temp. Evaporación		Conexiones		Calderín		Capilar	
		- 25°C	- 10°C	Línea Líquido	Línea Aspiración	Aire			
						Código	€	Código	€
SC-12CL	1/3	610	1.200	1/4"	3/8"	UC0450	484	UC0453	434
SC-15CL	3/8	730	1.450	1/4"	3/8"	UC0456	509	UC0459	459
SC-18CL	1/2	855	1.670	1/4"	3/8"	UC0462	618	UC0465	572