



**CENTRALES FRIGORÍFICAS COMPACTAS - COPELAND**

Temperatura gas de aspiración 25° C.

**PRECIOS: CONSULTAR**

**R-404A**

Modelo	Temp. Amb. °C.	Capacidad W. Temperatura de evaporación Media Temperatura						Comp.	Dimensiones mm.			Rec. Liq. l.	Peso Kg.
		+5° C	0° C	- 5° C	- 10° C	- 15° C	- 20° C		A	B	H		
		TM-510	45	90.750	75.870	62.850	51.540		41.760	33.330	D3DA 75X		
	50	81.630	68.190	56.460	46.290	37.500	29.910						
TM-610	45	105.990	88.860	73.890	60.900	49.620	39.930	D3DC 100X	2.350	1.200	1.600	2x24	1.180
	50	95.370	79.890	66.420	54.750	44.640	35.940						
TM-810	45	139.200	117.150	97.860	81.090	66.600	54.120	D3DS 150X	2.350	1.200	1.600	3x24	1.190
	50	125.010	105.120	87.810	72.810	59.850	48.690						
TM-910	45	157.890	132.330	110.040	90.660	73.890	59.400	D4DA 200X	2.350	1.200	1.600	3x24	1.290
	50	141.900	118.740	98.550	81.030	65.910	52.800						
TM-1200	45	196.470	165.360	138.180	114.570	94.140	76.500	D4DH 250X	2.350	1.200	1.600	3x24	1.330
	50	177.180	148.980	124.410	103.110	84.660	68.730						
TM-1400	45	227.640	191.670	160.260	133.020	109.440	89.100	D4DJ 300X	2.350	1.200	1.600	4x24	1.350
	50	204.060	171.630	143.400	118.950	97.830	79.560						
TM-1700	45	293.910	247.230	206.460	171.060	140.430	113.970	D6DH 350X	2.500	1.200	1.600	4x24	1.450
	50	264.480	222.240	185.430	153.540	125.940	102.060						
TM-2000	45	341.100	287.130	239.910	198.900	163.440	132.810	D6DJ 400X	2.500	1.200	1.600	1x130	1.490
	50	305.100	256.500	214.410	177.420	145.680	118.230						
TM-2400	45	410.700	344.400	286.590	236.430	192.690	155.160	D8DH 500X	2.500	1.200	1.600	1x150	1.700
	50	370.500	310.500	258.060	212.610	173.340	139.470						

Mod.	Temp. Cond. °C	Baja Temperatura						Comp.	Dimensiones mm.			Rec. Liq. l.	Peso Kg.
		- 20° C	- 25° C	- 30° C	- 35° C	- 40° C	- 45° C		A	B	H		
TL-180	45	38.010	30.060	23.295	17.550	12.705	8.640	D3DC 75X	2.350	1.100	1.600	2x24	1.150
	50	34.080	26.775	20.565	15.300	10.860							
TL-250	45	51.660	41.460	32.760	25.365	19.140	13.905	D3DS 100X	2.350	1.100	1.600	2x24	1.180
	50	46.680	37.350	29.430	22.725	17.070							
TL-360	45	75.210	60.030	47.100	36.150	26.880	19.020	D4DL 150X	2.350	1.200	1.600	3x24	1.320
	50	67.500	53.610	41.820	31.830	23.335							
TL-420	45	86.700	69.360	54.630	42.180	31.650	22.680	D4DT 220X	2.350	1.200	1.600	4x24	1.350
	50	76.860	61.200	47.910	36.690	27.135							
TL-530	45	108.270	86.790	68.520	53.040	39.900	28.755	D6DL 270X	2.500	1.200	1.600	4x24	1.430
	50	96.360	76.920	60.420	46.410	34.500							
TL-640	45	130.170	104.460	82.590	64.080	48.390	35.040	D6DT 300X	2.500	1.200	1.600	1x130	1.490
	50	116.760	93.390	73.530	56.670	42.360							
TL-800	45	158.580	127.020	100.200	77.430	58.110		D8DL 370X	2.500	1.200	1.600	1x150	1.700
	50	142.470	113.640	89.160	68.370								





**CENTRALES FRIGORÍFICAS COMPACTAS - FRASCOLD**

Temperatura gas de aspiración 25° C.

**PRECIOS: CONSULTAR**

**R-404A**

Mod.	Temp. Cond. °C.	Capacidad W.						Comp.	Dimensiones mm.			Rec. Líq. l.	Peso Kg.
		Temperatura de evaporación Media Temperatura							A	B	H		
		+5° C	0° C	- 5° C	- 10° C	- 15° C	- 20° C						
FM 250	45	43.380	36.300	30.150	24.930	20.280	16.260	F4 16Y	2.050	950	1.400	1x24	690
	50	39.240	32.850	27.240	22.440	18.180	14.520						
FM 300	45	51.630	43.350	36.120	29.970	24.510	19.830	F4 19Y	2.050	950	1.400	1x24	690
	50	46.830	39.300	32.700	27.090	22.080	17.790						
FM 330	45	56.790	47.640	39.660	32.880	26.850	21.690	F5 21Y	2.050	950	1.400	1x24	690
	50	51.450	43.170	35.880	29.700	24.180	19.440						
FM 380	45	66.900	55.830	46.170	37.950	30.630	24.390	Q5 25Y	2.050	950	1.400	2x24	710
	50		50.340	41.520	34.020	27.330	21.600						
FM 430	45	75.540	63.030	52.140	42.840	34.590	27.540	Q7 28Y	2.050	950	1.400	2x24	710
	50	68.190	56.820	46.890	38.400	30.870	24.390						
FM 490	45	85.140	71.430	59.460	49.260	40.200	32.460	Q7 33Y	2.050	950	1.400	2x24	710
	50		64.680	53.790	44.460	36.210	29.100						
FM 600	45	103.260	86.640	72.150	59.820	48.870	39.450	S10 39Y	2.350	1.000	1.600	2x24	940
	50	93.600	78.510	65.310	54.030	44.010	35.400						
FM 760	45	133.590	111.810	92.820	76.620	62.250	49.920	S15 51Y	2.350	1.000	1.600	3x24	958
	50	120.870	101.070	83.730	68.940	55.830	44.520						
FM 880	45	153.150	128.280	106.590	88.110	71.730	57.660	S20 56Y	2.350	1.000	1.600	3x24	976
	50	138.630	116.040	96.270	79.410	64.410	51.540						
FM 1070	45	186.540	156.090	129.540	106.890	86.820	69.570	V25 71Y	2.350	1.200	1.600	3x24	1.150
	50	168.720	141.060	116.850	96.180	77.820	62.040						
FM 1280	45	222.450	186.450	155.040	128.280	104.550	84.180	V30 84Y	2.350	1.200	1.600	4x24	1.160
	50	201.450	168.750	140.130	115.680	93.990	75.360						
FM 1420	45	247.260	207.240	172.320	142.560	116.190	93.540	V32 93Y	2.350	1.200	1.600	4x24	1.180
	50	223.830	187.560	155.730	128.580	104.460	83.730						
FM 1580	45	273.270	229.050	190.470	157.560	128.400	103.380	V35 103Y	2.350	1.200	1.600	4x24	1.190
	50	247.500	207.300	172.140	142.110	115.440	92.520						





**CENTRALES FRIGORÍFICAS COMPACTAS - FRASCOLD**

Temperatura gas de aspiración 25° C.

**PRECIOS: CONSULTAR**

**R-404A**

Mod.	Temp. Cond. °C	Capacidad W. Temperatura de evaporación Baja Temperatura						Comp.	Dimensiones mm.			Rec. Líq. l.	Peso Kg.
		- 20° C	- 25° C	- 30° C	- 35° C	- 40° C	- 45° C		A	B	H		
		FL 90	45	19.830	15.750	12.360	9.390		6.960	4.710	F4 19Y		
	50	17.790	14.070	10.950	8.250	6.000							
FL 105	45	21.900	17.430	13.710	10.470	7.770	5.310	F4 21Y	2.050	950	1.400	1x24	690
		50	19.680	15.600	12.180	9.180	6.720						
FL 107	45	24.270	19.260	14.700	10.710	7.410	4.410	Q4 25Y	2.050	950	1.400	1x24	692
		50	21.960	16.950	12.750	9.090	6.060						
FL 120	45	27.930	21.750	16.590	12.090	8.370	4.980	Q5 28Y	2.050	950	1.400	2x24	710
		50	24.780	19.140	14.370	10.260	6.840						
FL 150	45	32.460	25.740	20.100	15.210	11.160	7.470	Q5 33Y	2.050	950	1.400	2x24	710
		50	29.100	22.920	17.760	13.260	9.540						
FL 190	45	39.990	31.860	25.080	19.170	14.280	9.840	S7 39Y	2.350	1.000	1.600	2x24	930
		50	35.970	28.530	22.290	16.890	12.390						
FL 245	45	52.140	41.340	32.310	24.480	17.970	12.060	S10 51Y	2.350	1.000	1.600	2x24	940
		50	46.770	36.870	28.560	21.360	15.390						
FL 265	55	57.660	45.480	35.250	26.400	19.050	12.360	S15 56Y	2.350	1.000	1.600	3x24	970
		60	51.540	40.380	30.990	22.860	16.080						
FL 330	65	71.910	56.700	43.980	32.970	23.790		V15 71Y	2.350	1.200	1.600	3x24	1.100
		70	64.260	50.370	38.670	28.560	20.130						
FL 415	75	86.280	68.820	54.180	41.490	30.930		V20 84Y	2.350	1.200	1.600	3x24	1.140
		80	77.640	61.620	48.180	36.540	26.850						
FL 460	85	95.880	76.470	60.180	46.080	34.350		V25 93Y	2.350	1.200	1.600	3x24	1.170
		90	86.280	68.460	53.520	40.560	29.790						
FL 510	95	105.990	84.510	66.510	50.910	37.980		V25 103Y	2.350	1.200	1.600	3x24	1.170
		100	95.100	75.660	59.160	44.820	32.940						

