



COMPRESORES HERMÉTICOS ROTATIVOS

R-22

Código	Modelo	Desplaz. (cm ³)	Potencia Frigorífica W (ARI)	COP	Cond. (μF/V)	Dimensiones (mm.)				€
						Altura	B	C	D	
CO4600	SD122CV	12,2	2.040	2,96	17/400	276,4	112,2	0	93	136,74
CO4601	SD156CV	15,6	2.650	3,05	25/400	276,4	112,2	0	93	142,04
CO4602	SL193SV	19,3	3.250	3,15	35/450	325,8	129,1	33,4	70	188,68
CO4603	SL222SV	22,2	3.740	3,15	35/450	325,8	129,1	33,4	70	191,86
CO4604	SL253SV	25,3	4.270	3,15	35/450	325,8	129,1	33,4	70	200,34
CO4605	SHY33M***U	30,7	5.165	2,99	50/400	325,2	139,1	41,4	70	213,06
CO4606	SHW33T***U	35,6	5.990	3,01	50/400	340,2	139,1	41,4	70	223,66
CO4607	SHV33Y***U	41,7	7.100	3,04	50/450	385,7	139,1	41,4	70	293,62
CO4608	THU33WC6-U	48,8	8.350	3,15	60/450	419,5	139,1	52,4	125	361,46

R-134a

CO4609	BSA645CV	6,45	692	2,35	6.5	201	92	21	67	110,24
--------	----------	------	-----	------	-----	-----	----	----	----	--------

R-407C

Código	Modelo	Desplaz. (cm ³)	Potencia Frigorífica W (ARI)	COP	Cond. (μF/V)	Dimensiones (mm.)				€
						Altura	B	C	D	
CO4610	CG433E	14,1	2.320	2,94	30/400	289	118,6	33,4	63	156,88
CO4611	CG633G	16,7	2.780	2,95	35/400	303	118,6	33,4	63	160,06
CO4612	CH733H	19,4	3.230	2,87	50/400	317,2	129,1	41,4	70	196,10
CO4613	CSL211CV	21,1	3.550	2,90	35/400	310,8	129,1	33,4	70	198,22
CO4614	CH833U	24,2	4.150	2,92	35/450	317,2	139,1	41,4	70	207,76
CO4615	CHY33M-U	30,7	5.250	2,93	50/450	340,2	139,1	41,4	70	220,48
CO4616	CHW33T	35,6	6.150	3,00	60/400	354,6	139,1	41,4	70	226,84
CO4617	CHV33Y	41,7	7.150	2,95	55/480	385,7	139,1	41,4	70	311,64
CO4618	CTHU33W	48,8	8.200	2,95	60/450	419,5	139,1	41,4	70	361,46

R-410A

Código	Modelo	Desplaz (cm ³)	Potencia Frigorífica W (ARI)	COP	Cond. (μF/V)	Dimensiones (mm.)				€
						Altura	B	C	D	
CO4620	ASG088CV	8,8	2.055	2,76	30/400	294	118,6	33,4	63	165,36
CO4621	ASG108CV.B7AT	10,84	2.550	2,77	35/400	294	118,6	33,4	63	173,84
CO4622	ASL135SV	13,5	3.250	2,9	35/450	309,7	129,1	33,4	109	186,56
CO4623	ASL155SV	13,5	3.700	2,9	35/450	309,7	129,1	33,4	109	218,36
CO4624	ASL180SVC7LU	18	4.350	2,9	35/450	309,7	129,1	33,4	109	230,02
CO4625	ASH218SV	21,8	5.180	2,9	60/400	329,2	140,1	41,4	125	240,62
CO4626	ASH264SV	26,4	6.310	2,85	50/450	329,2	140,1	41,4	125	314,82
CO4627	ATH280SV	28	6.860	2,88	60/450	388,7	140,1	52,4	125	329,66
CO4628	ATH325CV	32,5	7.760	2,85	60/450	388,7	140,1	52,4	125	343,44

CONDICIONES ARI:

Temp. Evaporación = 7,2°C.

Temp. Condensación = 54,4°C.

Temp. Ambiente= 35°C

Temp. Líquido = 46,1°C.

Temp. Gases de retorno = 18,3°C

Compresores monofásicos 220V. 50 Hz.

