


EVAPORADORES BAJA VELOCIDAD DE AIRE - SERIE FBV

PASO DE ALETAS: 4,2 mm.

R-404A

| Modelo | FBV 15 | FBV 25 | FBV 42 | FBV 47 | FBV 61 | FBV 69 | |
|--|-------------------|---------|---------|---------|---------|---------|---------|
| Capacidad $\Delta T_1 = 8K - W$ (ENV 328 cond. 2) | 2.000 | 2.600 | 3.700 | 4.500 | 5.700 | 6.900 | |
| Caudal de aire | m ³ /h | 1.300 | 1.200 | 1.950 | 2.000 | 3.000 | 3.100 |
| Superficie | m ² | 13,8 | 27,6 | 34,1 | 55,1 | 51,1 | 82,7 |
| Volumen interior | dm ³ | 2,8 | 5,5 | 6,6 | 10,6 | 9,8 | 15,7 |
| Motoventiladores 230V//50Hz 1.350 r.p.m. | Nº x Ø | 2 x 230 | 2 x 230 | 2 x 300 | 2 x 300 | 2 x 300 | 2 x 300 |
| | A | 0,70 | 0,70 | 0,44 | 0,44 | 0,76 | 0,76 |
| | W | 70 | 70 | 100 | 100 | 160 | 160 |
| Nivel sonoro | dB(A) | 36 | 36 | 37 | 37 | 40 | 40 |
| Desescarche Eléctrico | Nº | 2 | 4 | 4 | 4 | 4 | 4 |
| | W | 1.700 | 3.400 | 5.600 | 6.800 | 8.400 | 10.200 |
| Conexiones | Entrada | 1/2" | 1/2" | 1/2" | 1/2" | 1/2" | 1/2" |
| | Salida mm | 16 | 22 | 22 | 22 | 28 | 28 |
| Peso neto | Kg. | 32 | 40 | 48 | 61 | 64 | 83 |
| Sin Desescarche | € | 1.060 | 1.300 | 1.750 | 2.130 | 2.190 | 2.710 |
| | Código | EV6670 | EV6671 | EV6672 | EV6673 | EV6674 | EV6675 |
| Desescarche Eléctrico | € | 1.150 | 1.473 | 1.966 | 2.374 | 2.459 | 3.015 |
| | Código | EV6680 | EV6681 | EV6682 | EV6683 | EV6684 | EV6685 |

La capacidad indicada corresponde a la potencia sensible del evaporador (superficie seca).

