





## EVAPORADORES COMERCIALES DE TECHO - SERIE P

Ventiladores de alta velocidad 1.350 r.p.m.

MODELOS P		Paso de aletas 3,5 - 7 mm.								
		P-21	P-42	P-63	P-85	P-105	P-115	P-127	P-144	P-172
Capacidad	$\Delta T$ 8°C - W	2.380	4.760	7.070	9.430	11.810	12.880	14.190	16.100	19.340
Dimensiones	A mm.	570	970	1.370	1.770	2.170	1.970	2.570	2.420	2.870
	B mm.	350	350	350	350	350	380	350	380	380
	C mm.	775	775	775	775	775	875	775	875	875
Superficie m <sup>2</sup>		10,9	21,8	32,7	43,6	54,5	49,2	65,4	61,5	73,8
Volumen interior dm <sup>3</sup>		2,5	4,9	7,3	9,7	12,1	11,0	14,5	13,6	16,3
Ventiladores	Nº x Ø (mm)	1x300	2x300	3x300	4x300	5x300	4x350	6x300	5x350	6x350
	Total Amperios I	0,30	0,60	0,90	1,20	1,50	1,40	1,80	1,75	2,10
	Total W.	60	120	180	240	300	580	360	725	870
	Caudal aire m <sup>3</sup> /h	1.400	2.800	4.200	5.600	7.000	8.600	8.400	10.750	12.900
	Flecha aire m.	7	7	7	7	7	8	7	8	8
Resistencias	W.	800	1.600	2.400	3.200	4.000	5.000	4.800	6.000	7.000
Conexiones	Entrada Ø Pulg.	1/2"	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
	Salida Ø Pulg.	1/2"	3/4"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"
	Desagüe Ø Pulg.	3/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Desescarche Aire	Código	EV0850	EV0851	EV0852	EV0853	EV0854	EV0855	EV0856	EV0857	EV0858
	€	944	1.486	2.053	2.655	3.180	3.628	3.793	4.477	5.291
Desescarche Eléctrico	Código	EV0865	EV0866	EV0867	EV0868	EV0869	EV0870	EV0871	EV0872	EV0873
	€	1.274	1.858	2.466	3.126	3.693	4.100	4.336	5.002	5.840

Ventiladores de baja velocidad 1.000 r.p.m.

MODELOS PB		Paso de aletas 3,5 - 7 mm.								
		PB-17	PB-34	PB-50	PB-67	PB-84	PB-88	PB-101	PB-110	PB-132
Capacidad	$\Delta T$ 8°C - W	1.900	3.770	5.640	7.520	9.400	9.900	11.280	12.350	14.830
Dimensiones	A mm.	570	970	1.370	1.770	2.170	1.970	2.570	2.420	2.870
	B mm.	350	350	350	350	350	380	350	380	380
	C mm.	775	775	775	775	775	875	775	875	875
Superficie m <sup>2</sup>		10,9	21,8	32,7	43,6	54,5	49,2	65,4	61,5	73,8
Volumen interior dm <sup>3</sup>		2,5	4,9	7,3	9,7	12,1	11,0	14,5	13,6	16,3
Ventiladores	Nº x Ø (mm)	1x300	2x300	3x300	4x300	5x300	4x350	6x300	5x350	6x350
	Total Amperios I	0,25	0,50	0,75	1,00	1,25	0,68	1,50	0,85	1,02
	Total W.	50	100	150	200	250	300	300	375	450
	Caudal aire m <sup>3</sup> /h	930	1.860	2.790	3.720	4.650	5.600	5.580	7.000	8.400
	Flecha aire m.	6	6	6	6	6	7	6	7	7
Resistencias	W.	800	1.600	2.400	3.200	4.000	5.000	4.800	6.000	7.000
Conexiones	Entrada Ø Pulg.	1/2"	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
	Salida Ø Pulg.	1/2"	3/4"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"
	Desagüe Ø Pulg.	3/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Desescarche Aire	Código	EV0950	EV0951	EV0952	EV0953	EV0954	EV0955	EV0956	EV0957	EV0958
	€	1.018	1.617	2.269	2.945	3.538	4.216	4.214	5.224	6.191
Desescarche Eléctrico	Código	EV0975	EV0976	EV0977	EV0978	EV0979	EV0980	EV0981	EV0982	EV0983
	€	1.336	2.000	2.688	3.405	4.045	4.693	4.757	5.737	6.727





## EVAPORADORES COMERCIALES DE TECHO - SERIE P

Ventiladores de alta velocidad 1.350 r.p.m.

MODELOS PA		Paso de aletas 2,7 mm.								
		PA-29	PA-58	PA-86	PA-114	PA-143	PA-153	PA-173	PA-191	PA-230
Capacidad	$\Delta T$ 8°C - W	3.600	7.200	10.790	14.380	17.970	19.170	21.570	23.950	28.760
Dimensiones	A mm.	570	970	1.370	1.770	2.170	1.970	2.570	2.420	2.870
	B mm.	350	350	350	350	350	380	350	380	380
	C mm.	775	775	775	775	775	875	775	875	875
Superficie m <sup>2</sup>		16	32	48	64	80	71,2	96	89	106,8
Volumen interior dm <sup>3</sup>		2,5	4,9	7,3	9,7	12,1	11,0	14,5	13,6	16,3
Ventiladores	Nº x Ø (mm)	1x300	2x300	3x300	4x300	5x300	4x350	6x300	5x350	6x350
	Total Amperios I	0,30	0,60	0,90	1,20	1,50	1,40	1,80	1,75	2,10
	Total W.	60	120	180	240	300	580	360	725	870
	Caudal aire m <sup>3</sup> /h	1.300	2.600	3.900	5.200	6.500	7.960	7.800	9.950	11.940
	Flecha aire m.	6	6	6	6	6	7	6	7	7
Resistencias	W.	800	1.600	2.400	3.200	4.000	5.000	4.800	6.000	7.000
Conexiones	Entrada Ø Pulg.	1/2"	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
	Salida Ø Pulg.	1/2"	3/4"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"
	Desagüe Ø Pulg.	3/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Desescarche Aire	Código	EV0900	EV0901	EV0902	EV0903	EV0904	EV0905	EV0906	EV0907	EV0908
	€	985	1.540	2.135	2.761	3.309	3.663	3.929	4.572	5.356
Desescarche Eléctrico	Código	EV0925	EV0926	EV0927	EV0928	EV0929	EV0930	EV0931	EV0932	EV0933
	€	1.315	1.911	2.536	3.221	3.805	4.135	4.477	5.097	5.893

Ventiladores de baja velocidad 1.000 r.p.m.

MODELOS PAB		Paso de aletas 2,7 mm.								
		PAB-22	PAB-44	PAB-68	PAB-89	PAB-111	PAB-118	PAB-134	PAB-148	PAB-178
Capacidad	$\Delta T$ 8°C - W	2.790	5.580	8.400	11.190	13.950	14.860	16.780	18.580	22.290
Dimensiones	A mm.	570	970	1.370	1.770	2.170	1.970	2.570	2.420	2.870
	B mm.	350	350	350	350	350	380	350	380	380
	C mm.	775	775	775	775	775	875	775	875	875
Superficie m <sup>2</sup>		16	32	48	64	80	71,2	96	89	106,8
Volumen interior dm <sup>3</sup>		2,5	4,9	7,3	9,7	12,1	11,0	14,5	13,6	16,3
Ventiladores	Nº x Ø (mm)	1x300	2x300	3x300	4x300	5x300	4x350	6x300	5x350	6x350
	Total Amperios I	0,25	0,50	0,75	1,00	1,25	0,68	1,50	0,85	1,02
	Total W.	50	100	150	200	250	300	300	375	450
	Caudal aire m <sup>3</sup> /h	860	1.720	2.580	3.440	4.300	5.200	5.160	6.500	7.800
	Flecha aire m.	5	5	5	5	5	6	5	6	6
Resistencias	W.	800	1.600	2.400	3.200	4.000	5.000	4.800	6.000	7.000
Conexiones	Entrada Ø Pulg.	1/2"	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"	5/8"
	Salida Ø Pulg.	1/2"	3/4"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"
	Desagüe Ø Pulg.	3/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Desescarche Aire	Código	EV1000	EV1001	EV1002	EV1003	EV1004	EV1005	EV1006	EV1007	EV1008
	€	1.065	1.682	2.340	3.045	3.650	4.275	4.356	5.318	6.244
Desescarche Eléctrico	Código	EV1015	EV1016	EV1017	EV1018	EV1019	EV1020	EV1021	EV1022	EV1023
	€	1.395	2.053	2.753	3.499	4.158	4.747	4.892	5.855	6.781

